

アイテム No. Item No.	呼び Nominal size	食付 ℓc	精度 Limit	形状 Type	形状寸法 (mm) Dimensions							ラジアル数 Radial	油溝数 Oil groove	新モデル New Model
					L	ℓ	Ds	ℓn	Dn	K	ℓk			
46980	M3 X 0.5	B	5	2	46	10	4	18	2.3	3.2	6	5	5	
46981	M3 X 0.5	B	6	2	46	10	4	18	2.3	3.2	6	5	5	
46982	M3 X 0.5	B	7	2	46	10	4	18	2.3	3.2	6	5	5	
46983	M3 X 0.5	P	5	2	46	10	4	18	2.3	3.2	6	5	5	
46984	M3 X 0.5	P	6	2	46	10	4	18	2.3	3.2	6	5	5	
46985	M3 X 0.5	P	7	2	46	10	4	18	2.3	3.2	6	5	5	
46986	M3.5 X 0.6	B	5	2	48	10	4	18	2.6	3.2	6	5	5	
46987	M3.5 X 0.6	P	5	2	48	10	4	18	2.6	3.2	6	5	5	
46988	M4 X 0.7	B	6	2	52	10	5	20	3	4	7	5	5	
46989	M4 X 0.7	B	7	2	52	10	5	20	3	4	7	5	5	
46990	M4 X 0.7	B	8	2	52	10	5	20	3	4	7	5	5	
46991	M4 X 0.7	P	6	2	52	10	5	20	3	4	7	5	5	
46992	M4 X 0.7	P	7	2	52	10	5	20	3	4	7	5	5	
46993	M4 X 0.7	P	8	2	52	10	5	20	3	4	7	5	5	
47850	M5 X 0.8	1C	6	2	60	10	5.5	22	3.9	4.5	7	5	5	★
46994	M5 X 0.8	B	6	2	60	10	5.5	22	3.9	4.5	7	5	5	
46995	M5 X 0.8	B	7	2	60	10	5.5	22	3.9	4.5	7	5	5	
46996	M5 X 0.8	B	8	2	60	10	5.5	22	3.9	4.5	7	5	5	
46997	M5 X 0.8	P	6	2	60	10	5.5	22	3.9	4.5	7	5	5	
46998	M5 X 0.8	P	7	2	60	10	5.5	22	3.9	4.5	7	5	5	
46999	M5 X 0.8	P	8	2	60	10	5.5	22	3.9	4.5	7	5	5	
47853	M6 X 1	1C	7	2	62	10	6	24	4.6	4.5	7	5	5	★
47000	M6 X 1	B	7	2	62	10	6	24	4.6	4.5	7	5	5	
47001	M6 X 1	B	8	2	62	10	6	24	4.6	4.5	7	5	5	
47002	M6 X 1	B	9	2	62	10	6	24	4.6	4.5	7	5	5	
47003	M6 X 1	P	7	2	62	10	6	24	4.6	4.5	7	5	5	
47004	M6 X 1	P	8	2	62	10	6	24	4.6	4.5	7	5	5	
47005	M6 X 1	P	9	2	62	10	6	24	4.6	4.5	7	5	5	
47006	M6 X 0.75	B	6	2	62	10	6	24	4.6	4.5	7	5	5	
47007	M6 X 0.75	P	6	2	62	10	6	24	4.6	4.5	7	5	5	
47008	M7 X 1	B	7	3	65	16	6.2	26	5.6	5	8	6	6	
47009	M7 X 1	P	7	3	65	16	6.2	26	5.6	5	8	6	6	
47010	M7 X 0.75	B	6	3	65	16	6.2	26	5.6	5	8	6	6	
47011	M7 X 0.75	P	6	3	65	16	6.2	26	5.6	5	8	6	6	
47856	M8 X 1.25	1C	7	3	70	18	6.2	30	6	5	8	6	6	★
47012	M8 X 1.25	B	7	3	70	18	6.2	30	6	5	8	6	6	
47013	M8 X 1.25	B	8	3	70	18	6.2	30	6	5	8	6	6	
47014	M8 X 1.25	B	9	3	70	18	6.2	30	6	5	8	6	6	
47015	M8 X 1.25	P	7	3	70	18	6.2	30	6	5	8	6	6	
47016	M8 X 1.25	P	8	3	70	18	6.2	30	6	5	8	6	6	
47017	M8 X 1.25	P	9	3	70	18	6.2	30	6	5	8	6	6	
47859	M8 X 1	1C	7	3	70	18	6.2	30	6	5	8	6	6	★
47018	M8 X 1	B	7	3	70	18	6.2	30	6	5	8	6	6	
47019	M8 X 1	P	7	3	70	18	6.2	30	6	5	8	6	6	
47860	M10 X 1.5	1C	7	3	75	19	7	32	6.8	5.5	8	8	8	★
47020	M10 X 1.5	B	7	3	75	19	7	32	6.8	5.5	8	8	8	
47021	M10 X 1.5	B	9	3	75	19	7	32	6.8	5.5	8	8	8	
47022	M10 X 1.5	P	7	3	75	19	7	32	6.8	5.5	8	8	8	
47023	M10 X 1.5	P	9	3	75	19	7	32	6.8	5.5	8	8	8	
47863	M10 X 1.25	1C	7	3	75	19	7	32	6.8	5.5	8	8	8	★
47024	M10 X 1.25	B	7	3	75	19	7	32	6.8	5.5	8	8	8	
47025	M10 X 1.25	B	9	3	75	19	7	32	6.8	5.5	8	8	8	
47026	M10 X 1.25	P	7	3	75	19	7	32	6.8	5.5	8	8	8	
47027	M10 X 1.25	P	9	3	75	19	7	32	6.8	5.5	8	8	8	
47866	M10 X 1	1C	7	3	75	19	7	32	6.8	5.5	8	8	8	★
47028	M10 X 1	B	7	3	75	19	7	32	6.8	5.5	8	8	8	
47029	M10 X 1	B	9	3	75	19	7	32	6.8	5.5	8	8	8	
47030	M10 X 1	P	7	3	75	19	7	32	6.8	5.5	8	8	8	
47031	M10 X 1	P	9	3	75	19	7	32	6.8	5.5	8	8	8	
47867	M12 X 1.75	1C	10	3	82	23	8.5	38	8.3	6.5	9	8	8	★
47032	M12 X 1.75	B	8	3	82	23	8.5	38	8.3	6.5	9	8	8	
47033	M12 X 1.75	B	10	3	82	23	8.5	38	8.3	6.5	9	8	8	
47034	M12 X 1.75	P	8	3	82	23	8.5	38	8.3	6.5	9	8	8	
47035	M12 X 1.75	P	10	3	82	23	8.5	38	8.3	6.5	9	8	8	
47870	M12 X 1.5	1C	10	3	82	23	8.5	38	8.3	6.5	9	8	8	★
47036	M12 X 1.5	B	7	3	82	23	8.5	38	8.3	6.5	9	8	8	
47037	M12 X 1.5	B	10	3	82	23	8.5	38	8.3	6.5	9	8	8	
47038	M12 X 1.5	P	7	3	82	23	8.5	38	8.3	6.5	9	8	8	
47039	M12 X 1.5	P	10	3	82	23	8.5	38	8.3	6.5	9	8	8	
47873	M12 X 1.25	1C	12	3	82	23	8.5	38	8.3	6.5	9	8	8	★
47040	M12 X 1.25	B	7	3	82	23	8.5	38	8.3	6.5	9	8	8	
47041	M12 X 1.25	B	12	3	82	23	8.5	38	8.3	6.5	9	8	8	
47042	M12 X 1.25	P	7	3	82	23	8.5	38	8.3	6.5	9	8	8	
47043	M12 X 1.25	P	12	3	82	23	8.5	38	8.3	6.5	9	8	8	
47876	M12 X 1	1C	9	3	82	23	8.5	38	8.3	6.5	9	8	8	★
47044	M12 X 1	B	7	3	82	23	8.5	38	8.3	6.5	9	8	8	
47045	M12 X 1	B	9	3	82	23	8.5	38	8.3	6.5	9	8	8	
47046	M12 X 1	P	7	3	82	23	8.5	38	8.3	6.5	9	8	8	
47047	M12 X 1	P	9	3	82	23	8.5	38	8.3	6.5	9	8	8	
47048	M14 X 1.5	B	10	3	88	25	10.5	42	10.3	8	11	8	8	
47049	M14 X 1.5	P	10	3	88	25	10.5	42	10.3	8	11	8	8	
47050	M16 X 1.5	B	10	3	95	27	12.5	45	12.3	10	13	8	8	
47051	M16 X 1.5	P	10	3	95	27	12.5	45	12.3	10	13	8	8	
47052	M18 X 1.5	B	11	3	100	29	14	48	13.8	11	14	8	8	
47053	M18 X 1.5	P	11	3	100	29	14	48	13.8	11	14	8	8	
47054	M20 X 1.5	B	11	3	105	30	15	50	14.8	12	15	8	8	
47055	M20 X 1.5	P	11	3	105	30	15	50	14.8	12	15	8	8	

・精度欄の は2級めねじ相当適応の推奨精度です。

・ The recommended tap limit in corresponds to JIS Class 2 internal thread standard.

・★の新モデルは2020年秋発売予定。

・ New model of ★ will be released in the fall of 2020.